

Features

- Supports the latest RFID technology
- Supports Mobile Access
- Supports Zigbee Online
- Fire listed (UL)
- ANSI BHMA certified
- EN certified
- ADA compliant
- Sustainable manufacturing processes and materials
- Aesthetically appealing anodized finishes available
- Designed for both indoor and outdoor
- use in all weather conditions
- Compatible with Vostio Access Management

Technical Data

Power	4,5 V DC (3 x AA alkaline batteries)
Battery Location	In inside escutcheon
Material	Handles & Roses: Aluminium (EN AW6063 T6), Plastic inside escutcheon, Steel and Stainless steel
Metal Finishes	Black matt anodized, Natural matt anodized, Gold matt anodized. More finishes will be added upon request
Standard Plastic Color	Black RAL 9005
Handle Options in Standard Range	VingCard standard handle, California handle
Emergency Opening Options	Electronic emergency opening with service unit.
User Interface	RGB LED (green, red, yellow, blue) and acoustic beeper
Locking Mechanism	Electro-mechanical locking mechanism located in the escutcheon.
Door Thickness	36 - 120 mm / 1,42 - 4,72 Inches
System Software Compatibility	Vostio Access Management
Online Compatibility	Wireless (based on ZigBee protocol)
Storage Temperature	0-70 °C / 32-158 °F: non-condensing environment.
Tested Operating Temperature	Tested from -25 °C to 70 °C (-13 °F to 158 °F), according to IEC 60068-2.
Certifications	Certified European EMC LVD and R&TTE Directives ANSI BHMA Fire approved according to UL (timber doors and metal doors) FCC/IC for US and Canada.
Mobile Access Support	Reader with built-in BLE or NFC-based digital wallet
Reader IP Rating	IP 56

